



## VIPER™ ELITE CLASSIC

3 FLAVOR FROZEN DISPENSER



### FEATURES

Building on nearly 50 years of experience, Viper Elite raises the bar in frozen with superior engineering and quality.

**Enhanced Reliability** – Increase uptime with the most reliable FCB dispenser on the market

**Syrup Flexibility** – Pressure transducers ensure you'll be able to perform as syrups change in the future

**Expand Drink Portfolios** – Individual barrel flexibility (FCB/FUB) and profile settings

**Intelligent Defrost™** – Patented adaptive defrost keeps you up and running during peak demand so you never miss a sale

**Information at your fingertips** - Quickly access manuals and easy-to-follow staff and service videos via QR code

**C3 Technology** – Cooling, carbonation, and controls provide unmatched drink profile consistency, builds repeat sales and minimizes syrup usage

**Programmable sleep mode** – Conserves energy in off hours

**Technician designed** – Reduced maintenance and service times

**ADA Compliant** – Stainless push handle valve

MODELS

PART NUMBER	DESCRIPTION
621360142	Viper Elite Classic 3 flavor, 230/60Hz, SPH Valve, Tall Merchandiser
621360042	Viper Elite Classic 3 flavor, 230/60Hz, Motorman Valve, Tall Merchandiser
621360141	Viper Elite Classic 3 flavor, 230/60Hz, SPH Valve, Short Merchandiser
621360041	Viper Elite Classic 3 flavor, 230/60Hz, Motorman Valve, Short Merchandiser
621350042	Viper Elite Classic 3 flavor, 230/50Hz, Motorman Valve, Tall Merchandiser
621350041	Viper Elite Classic 3 flavor, 230/50Hz, Motorman Valve, Short Merchandiser
621360142EU	Viper Elite Classic 3 Flavor, 230/60Hz, SPH Valve, Tall Merchandiser, IEC Power Cord

SPH stands for Stainless Push Handle. For FUB applications, Motorman valves are recommended.

ACCESSORIES

PART NUMBER	DESCRIPTION
629087406	Leg kit, 4" legs adjustable to 5.25"
620053990	Viper 3 flavor cart, stainless steel
620046410	Viper 3 flavor generic graphic for tall merchandiser
620047173	Viper 3 flavor generic graphic for short merchandiser
620042868	Generic flavor card set (includes 18 flavors)
325674000	Buck and boost transformer

Refer to installation accessory guideline for complete list.

TECHNICAL SPECIFICATIONS

**ELECTRICAL RATINGS** . . . . . 230V +/- 15V 60Hz, 30a, single phase  
 230V +/- 15V 50HZ, 30a, single phase  
 (includes 8ft. power cord NEMA L6-30P  
 molded plug connection. Part Numbers ending  
 in "EU" and 50Hz SKUs include 8ft. power cord  
 IEC60309 32 Amp molded plug connection)

**PRESSURE REQUIREMENTS** . . . CO2 = 75 psig  
 Water = 25 min. psig dynamic

**DRAW CAPACITY** . . . . . 75-82 oz/min. continuous, alternating  
 barrels @ 75°F ambient

**REFRIGERATION** . . . . . 19,000 BTU, R404A




**MINIMUM CLEARANCE  
 REQUIRED** . . . . . Top: 12"  
 Each side: 2" or Back: 2"

**UNIT DIMENSIONS** . . . . . 22.75"W x 32.5"D x 43.7"H  
 (tall merchandiser)  
 22.75"W x 32.5"D x 37"H  
 (short merchandiser)

**GRAPHIC CARD DIMENSIONS** . . . 22.5"W x 18.75"H  
 (tall merchandiser)  
 22.5"W x 11.79"H  
 (short merchandiser)

**FLAVOR CARD DIMENSIONS** . . . 6.5"W x 4"H

**SHIPPING WEIGHT** . . . . . 465 lbs; cart 175 lbs

**AGENCY LISTINGS** . . . . . 60 Hz     
 . . . . . 50 Hz 